



EXPERT 54

NEW

ALUMINIUM. PROFESSIONAL USE

PRODUCT +

FOR DURABLE PERFORMANCE

PATENT

High resistance cast aluminium hinges, covering the profiles on both sides.



Wide and resistant platform in cast aluminium

Size 300 x 290 x 250 mm.

The shape of the platform naturally prevents it from lifting up.



REGISTERED DESIGN

The best step-to-stile assembly on the market thanks to the high-pressure die-cast aluminium anti-rotation reinforcements on the steps: maximum stability and durability. ⁽¹⁾



Front stiles painted white. Keeps hands clean.



Wide non-slip steps = 85 mm.

Rear section strengthened by a tread. ⁽²⁾


Wide non-slip feet, screwed to the stiles : more surface resting on the floor for more stability.



REGISTERED DESIGN



EXPERT 54
5 steps



EXPERT 54 - 5 STEPS



EXPERT 54 - 5 STEPS

TESTED AT 300 KG*

Tests carried out in working conditions, the 4 legs resting on a concrete floor with a load of 300 kg applied to the platform.

Maximum load capacity 150 kg.

Item code							
		(m)	(m)	(m)	(m)	(kg)	
429203	3172964292030	3	0,66	2,65	1,50 x 0,50 x 0,17	5,35	
429204	3172964292047	4	0,88	2,90	1,75 x 0,55 x 0,17	6,35	
429205	3172964292054	5	1,10	3,10	2,00 x 0,60 x 0,17	7,40	
429206	3172964292061	6	1,32	3,30	2,25 x 0,63 x 0,17	8,60	
429207	3172964292078	7*	1,54	3,55	2,50 x 0,67 x 0,17	10,30	
429208	3172964292085	8*	1,76	3,75	2,71 x 0,71 x 0,17	11,15	
429210	3172964292108	10*	2,20	4,20	3,20 x 0,79 x 0,22	15,35	
429212	3172964292122	12*	2,64	4,65	3,70 x 0,86 x 0,22	20,80	

(1) Platform included. (2) Working height = platform height + 2 m.

*Equipped with safety straps starting from 7-step models. Optional handrails (1,24 m/4 ft.) starting from 7-step models.

NF
Decree 96-333
Standard EN 131.
5-year warranty