







## Rekola Reflex AbrasiveSoft cloth



Product code	Color code	Dimension	
10-7050	4 colour tags	55 x 23 cm	<b>Rekola Reflex</b> AbrasiveSoft cloth Multiple-use 86 grs
<b>Packed</b>	5 pcs pp bag  30 pcs 5-pack per transport box		
<b>Where:</b>	Hard top and ceramic safety floors for hygienic cleaning results: e.g. toilet and bath facilities at healthcare, nursery, school, university, office, public building, hospitality and residential. Floors at sport facilities, food industry, locker rooms etc.		
<b>How:</b>	<p>In conjunction with <b>Rekola Reflex</b> 50 cm squeegee and <b>Rekola Reflex</b> 100/180 extendable handle</p> <p>As preparation on a cleaning trolley <b>charge cloths in a closed container</b> like a. 6 Ltr. rectangle bucket with lid. Put the cloths inside and pour equally the terminated fluid over the cloths, leave for a while with closed lid.  <b>Alternatively charge cloths in a washing machine</b>, by adapting the spinning of the last rinse.  <b>Avoid</b> overdosing, bleach and softeners</p>		
<b>Charge:</b>	<p>With clean water; optional diluted with for UMF suitable chemical according supplier instruction  <i>Please be aware that some chemicals may cause damage to user, material and environment</i>            Depending on floor circumstances charge the cloths with 100-180 ml per cloth;  <b>Regardless the charging liquid: avoid overdosing</b></p>		
Eco Labeled:	 3083 0027		

# REKOLA

Maintenance																					
<b>Laundry:</b>	   																				
<b>Washing:</b>	rinse twice assuring all cleaning chemicals are removed main program for synthetic fibers at 95°C, for environmental reasons at 60° C or less is preferred rinse twice assuring all laundry agents are removed temperatures and water volume according																				
	tumble drying at lower heat																				
	do not use bleach or softener																				
	low water level during processing or overloading washing machine (max a. 80% of door window) may cause irreversible damage to cloths.																				
<b>Disinfection:</b>	non –bleach disinfectant* laundry agent and autoclaving may be used if required *e.g. peroxide based; this may affect colors																				
<b>Durability:</b>	500 washing cycles. Rough surfaces like safety flooring will reduce lifetime expectations																				
<b>Disposable:</b>	Rekola Reflex AbrasiveSoft cloths are purely synthetics: may be used for recycling programs; or because of their high energy value and with no other than CO <sub>2</sub> and water as emission, safely disposed by controlled energy-supply programs.																				
Components																					
<b>Body:</b>	<b>50% split Ultra Microfiber and 50 % PET film 90% PES 10 PA and F= 0,154 Dtex</b>																				
<b>Borders:</b>	<b>100% PES</b>																				
Characteristics																					
<b>Shrinkage:</b>	< 5% at recommended washing instructions																				
<b>Color fastness</b>	4-5 <i>standard request ≥ 3-4</i>																				
<b>Charging</b>	4,2 DAC value <i>standard request minimum 2,5</i>																				
<b>Abrasion</b>	The abrasion generated during usage, is not advised for usage on softer material surfaces; such as Polycarbonates.																				
<b>Weber &amp; Leucht S301/1.3 dirt removal</b>	<table><tr><td>Ceramic Tile SF 11</td><td>Dust A23</td><td>Damp</td><td>93%</td><td><i>standard request ≥ 70</i></td></tr><tr><td>PVC- Flooring PL-03</td><td>Dust A23</td><td>Damp</td><td>87%</td><td><i>standard request ≥ 70</i></td></tr><tr><td>Ceramic Tile SF 11</td><td>Muddy dirt A05</td><td>Damp</td><td>100%</td><td><i>standard request ≥ 70</i></td></tr><tr><td>PVC- Flooring PL-03</td><td>Muddy dirt A05</td><td>Damp</td><td>100%</td><td><i>standard request ≥ 70</i></td></tr></table>	Ceramic Tile SF 11	Dust A23	Damp	93%	<i>standard request ≥ 70</i>	PVC- Flooring PL-03	Dust A23	Damp	87%	<i>standard request ≥ 70</i>	Ceramic Tile SF 11	Muddy dirt A05	Damp	100%	<i>standard request ≥ 70</i>	PVC- Flooring PL-03	Muddy dirt A05	Damp	100%	<i>standard request ≥ 70</i>
Ceramic Tile SF 11	Dust A23	Damp	93%	<i>standard request ≥ 70</i>																	
PVC- Flooring PL-03	Dust A23	Damp	87%	<i>standard request ≥ 70</i>																	
Ceramic Tile SF 11	Muddy dirt A05	Damp	100%	<i>standard request ≥ 70</i>																	
PVC- Flooring PL-03	Muddy dirt A05	Damp	100%	<i>standard request ≥ 70</i>																	
<b>Bacteria reduction</b>	E-coli 99,89% log 2,96      S.aureus 99,31 log 2,16																				
<b>Non-Touch</b>	In conjunction with Rekola Reflex squeegee tool, dirty cloths are not touched when demounting.																				
<b>Patent:</b>	F1201000028 Floor Maintenance Device and Cloth																				
Guarantee																					
500 times use and wash in general hygiene cleaning circumstances at a maintained non-safety sealed floor. More usages can be achieved if considering optimal laundry and cleaning conditions. For instruction and details ask your distributor.																					